

PATENT

Atty. Dkt. No. MRKS0130

**IN THE CLAIMS:**

Please amend the claims as follows:

1. (Currently Amended) An apparatus for orientating a work tool, the apparatus comprising:
  - a first anchor,
  - an energy unit,
  - a programmable controller,
  - an axial displacement part,
  - a rotational part configured to rotationally orient the work tool about a longitudinal axis of the apparatus, and
  - a second anchor,wherein:
  - the axial displacement part is located between the first anchor and the second anchor,
  - at least one of the axial displacement part and the rotational part is controllable by the programmable controller so that the work tool can be steered along any path within a work area, and
  - the ~~cutting~~ work tool is a high pressure water cutter.
2. (Original) An apparatus as claimed in claim 1, wherein the axial displacement part comprises a telescopic member.
3. (Original) An apparatus as claimed in claim 2, wherein the relative position of the telescopic member is transmittable to the controller by means of a position transmitter.
4. (Original) An apparatus as claimed in claim 1, wherein the relative position of the rotational part is transmittable to the controller by means of an angle transmitter.

Page 2

457542\_1

## PATENT

Att. Dkt. No. MRKS/0130

5. (Cancelled)
6. (Previously Presented) An apparatus as claimed in claim 1, wherein the work tool is operably coupled to the axial displacement part or rotational part.
7. (Original) An apparatus as claimed in claim 6, wherein the work tool is a cutting tool.
8. (Canceled)
9. (Currently Amended) A method of orientating a work tool in a cased wellbore, comprising:  
directing the work tool with an axial displacement part and a rotational part operably connected to at least one of a first and second anchor,  
wherein:  
the axial displacement part is positioned between the first anchor and the second anchor, and  
at least one of the axial displacement part and rotational part is controlled by a programmable controller;  
releasing the first anchor;  
moving the first anchor to a new position in the cased wellbore;  
setting the first anchor at the new position in the cased wellbore; and  
releasing the second anchor.
10. (Previously Presented) An apparatus as claimed in claim 1, wherein the axial displacement part comprises a piston rod.
11. (Previously Presented) An apparatus as claimed in claim 1, wherein the rotational part is coupled to the second anchor.

## PATENT

Atty. Dkt. No. MARKS/D130

12. (Previously Presented) An apparatus as claimed in claim 2, wherein the rotational part is coupled to the telescopic member.

13. (Canceled)

14. (Currently Amended) An apparatus for orientating a work tool, the apparatus comprising:

a first anchor,

an energy unit,

a programmable controller,

an axial displacement part,

a rotational part configured to rotationally orient the work tool about a longitudinal axis of the apparatus, and

a second anchor,

wherein:

the axial displacement part is located between the first anchor and the second anchor,

at least one of the axial displacement part and the rotational part is controllable by the programmable controller so that the work tool can be steered along any path within a work area,

the axial displacement part comprises a telescopic member, and

the relative position of the telescopic member is transmittable to the controller by means of a position transmitter.

15. (Currently Amended) An apparatus for orientating a work tool, the apparatus comprising:

a first anchor,

an energy unit,

a programmable controller,

an axial displacement part,

a rotational part, and

## PATENT

Atty. Dkt. No. MRKS/0130

a second anchor,

wherein:

the axial displacement part is located between the first anchor and the second anchor,

at least one of the axial displacement part and the rotational part is controllable by the programmable controller so that the work tool can be steered along any path within a work area, and

the relative position of the rotational part is transmittable to the controller by means of using an angle transmitter.

Please add the following new claim.

16. (New) An apparatus as claimed in claim 1, wherein the work tool is operable to cut through a cased wellbore.

17. (New) The method of claim 9, further comprising rotating the rotational part to rotationally orient the work tool about a longitudinal axis of the apparatus.

18. (New) An apparatus as claimed in claim 15, wherein the rotational part is configured to rotationally orient the work tool about a longitudinal axis of the apparatus.

19. (New) An apparatus as claimed in claim 15, wherein the work tool is a cutting tool.

20. (New) An apparatus for orientating a work tool, the apparatus comprising:  
a first anchor;  
a second anchor;  
an axial displacement part located between the first anchor and the second anchor; and

**PATENT**

Any. Dkt. No. MRKS/0130

a rotational part configured to rotationally orient the work tool about a longitudinal axis of the apparatus, wherein actuation of the rotational part steers the work tool along a path within the work area.

21. (New) The apparatus of claim 20, wherein the relative position of the rotational part is transmittable to a controller using an angle transmitter.